


DPZ-L



Pneumatic sealer for steel strap



Double throughout

Two are better than one – a phrase that may not always be true but hits the nail on the head when it comes to this tool. And that on two levels. On the one hand, it concerns joining. At the single push of a button, the DPZ-L generates two notches in the seal.

This self-contained notching process guarantees the highest degree of joint reliability and easy handling. Added to this is the enormous time savings thanks to the process of double notching. In addition, the DPZ-L is very easy to maintain thanks not least to the two air chambers in this sealer making the use of springs unnecessary and the entire tool less vulnerable. "Less vulnerable" is an understatement as the DPZ-L has repeatedly proven itself in practice through its robustness like the PR33, the tensioner matching the SPZ-L.

Together they stand for maximum reliability in heavy-duty strapping applications.

Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK, RSL
Dimensions	13.4 x 5.9 x 11.2" (L x W x H)
Weight	9.9 lb
Air pressure	max. 6 bar flow pressure

Copyright TITAN Umreifungstechnik, GmbH & Co. KG | Berliner Straße 51-55 | 58332 Schwelm | Deutschland
 Kontakt: Judy Riddle | 704-663-2490 | jriddle@titanstrapping.com

Strap/Joint

Type of strap	Steel strap
---------------	-------------

Strap	Automatenband MEGABAND®
Strap width	3/4" ; 1" (series 1) 1 1/4" (series 2)
Strap thickness	0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)
Kind of seal	Seal-joint (double notch)

Application

Strapping of packages and palletized goods with small contact surfaces.