

# Mytho Auto Pallet Wrapping Machine

## XF-6013



The Mytho XF-5013 is our top of the range automatic pallet wrapping machine, with powered prestretch carriage (PPS) designed for users wrapping upto 100 X 2000KG pallets a day who are looking for a quality-built machine with some customisable wrapping options. The PPS carriage allows users to achieve maximum savings per pallet wrapped.

### Main Features

- Auto height detection
- Automatic clamping system
- Automatic hotwire cutting and press to finish wrapping
- Powered prestretch head unit, electronically programable.
- 2000kg Capacity
- 2500mm Wrapping height
- 1800mm turntable for AU pallets.
- Touchscreen Interface
- 6 Programable Cycles
- Semi auto and manual mode
- Adjustable turntable speed
- Adjustable top and bottom wrap number
- Adjustable amount of wrapping applied
- Fully enclosed mast



### Technical features

<b>Max load weight</b>	2000kg	<b>Load height sensing photocell</b>	Yes
<b>Max wrapping height</b>	2500mm	<b>Emergency Mushroom stop</b>	Yes
<b>Turntable Height</b>	78mm	<b>Beeper at start and stop</b>	Yes
<b>Turntable Diameter</b>	1650mm	<b>Safety Crush device under carriage</b>	Yes
<b>Power</b>	230v/10amp AU STD plug.	<b>Auto Mode</b>	Yes
<b>Film carriage</b>	200% PRESTRETCH	<b>Inverters</b>	Schneider
<b>Film core Size</b>	76mm	<b>Forklift transportable</b>	Yes
<b>Turntable Drive</b>	Chain		
<b>Mast Drive</b>	Internal Chain		
<b>Limit switch Location</b>	Inside of mast.		

The Mytho is a high customizable wrapping platform, specifications such as turntable size, wrapping height and many other options including interchangeable carriages, can be ordered from the factory.

### PARAMETERS ADJUSTABLE FROM CONTROL PANEL:

- Bottom pallet wrapping rounds
- Top pallet wrapping rounds from 1
- Rotation speed adjustable from 5 to
- Spool carriage speed **upwards** and **downwards** independently adjustable
- Spool carriage speed **upwards** speed from 1,3 up to 5,4 m/min
- Spool carriage speed **downwards** speed from 1,3 up to 5,4 m/min
- All function parameters settable on display
- Photocell sensing delay
- All function parameters settable on display
- Weight of film used (Option on PRS – PS)

from 1 to 10  
to 10  
12 rpm



#### **BASIC CYCLES SELECTABLE FROM CONTROL PANEL:**

- Double cycle (Upwards / Downwards)
- Single cycle (Only upwards or only downwards)
- Top sheet cycle
- Wrapping cycle with altimeter (Photocell Off)
- Wrapping cycle with start and stop height pre-programmed
- Wrapping cycle with reinforcement and settable number of wraps
- Wrapping cycle with step rising of spool carriage
- Manual wrapping programme
- Push-buttons for manual functions

#### **POWERED PRESTRETCH(PRS) FILM CARRAIGE:**

- Capable of 150%-250 stretch (350% with PS Carriage)
- Electronically settable tension
- Saves upto 50% on wrapping costs
- Low maintenance and minimal parts design

